



1900 Albany Place SE  
P.O. Box 286  
Orange City, IA 51041

800-747-3436 Fax 712-737-3893  
www.oldmastrs.com

## PRODUCT INFORMATION

### **SUPER VARNISH SATIN**

<b>PRODUCT NO.</b>	49301, 49304, 49305, 49308
<b>GENERIC TYPE</b>	"Conventional" Alkyd Varnish
<b>COLOR</b>	Clear, may be tinted sparingly with universal colorant
<b>GLOSS</b>	25 to 30 @ 60°
<b>SOLIDS BY WEIGHT</b>	44.0 to 45.0%
<b>SOLIDS BY VOLUME</b>	36.5%
<b>V.O.C.</b>	458 grams/liter
<b>THEORETICAL COVERAGE @ 1 MIL DFT</b>	578 sq. ft. per gal.
<b>COVERAGE @ RECOMMENDED DFT</b>	350 to 400 sq. ft. per gal.
<b>RECOMMENDED DFT PER COAT</b>	1½ Mils
<b>WEIGHT PER GALLON</b>	7.6 lbs.
<b>FLASH POINT</b>	102°F Closed Cup
<b>USE</b>	Use on all types of new or old wood surfaces. Can be used over old steared finishes.
<b>VISCOSITY AT 77°F</b>	35 to 40 sec. #4 Ford Cup
<b>AVERAGE DRY TIME AT 70°F &amp; 50% R.H.</b>	3 hours dry to touch, recoat after 8 to 16 hours
<b>RECOMMENDED THINNER</b>	Do not thin unless surface temperature requires it. Thin 5% with mineral spirits or VM&P Naphtha if necessary.
<b>APPLICATION</b>	Brush, roller, sprayer or flat applicator
<b>SURFACE PREPARATION</b>	All previously sealed and finished surfaces must be deglossed with a fine grit sandpaper followed by a tack rag to clean surface.
<b>CLEAN UP</b>	Mineral Spirits

**FOR THE LOVE OF WOOD®**

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



# PRODUCT INFORMATION

## **SUPER VARNISH SATIN**

**DESCRIPTION:** OLD MASTERS® SUPER VARNISH is a traditional alkyd resin varnish of the highest quality. It provides a beautiful resilient finish that is highly resistant to water and yellowing caused by age. SUPER VARNISH may be used on interior wood surfaces such as furniture, woodwork, shelving, and doors. It is compatible with most finishes and is an excellent product to use on bare wood or to apply to previously varnished, lacquered, or stained surfaces that are free of waxes, silicones, household greases, or other substances which would hinder adhesion. SUPER VARNISH can be applied over finishes containing stearates. It is not recommended for floors or exterior surfaces.

**THINNING:** Do not thin. Use as packaged.

**SURFACE PREPARATION:** The wood surface must be clean, dry, and free from dirt, dust, wax, and grease. **Surfaces must be properly prepared prior to application of this product.**

**Bare Wood Surfaces:** Eliminate imperfections by sanding the wood thoroughly; begin with a medium grit sandpaper progressing to a fine grit. Always sand in the direction of the woodgrain. Remove dust particles with a tack rag.

**Previously Finished Wood:** Sand with a fine grit sandpaper to remove surface imperfections and gloss. Remove sanding dust with a tack rag. Wax and/or polish are best removed by wiping thoroughly with mineral spirits. Change rags often and wash until all wax and/or polish is removed.

**APPLICATION INSTRUCTIONS:** Stir well before and during use. For projects requiring more than one container, intermix to ensure gloss uniformity. Equipment must be clean prior to start. Flush airless lines with mineral spirits. Apply by brush, pad, roller, or airless spray. A good quality natural bristle brush will make application easier. Use of a 1/4" nap mohair or foam roller, lambskin pad type applicator, or airless tip size of .013 to .015 is recommended. Two (2) coats are recommended for best results. For high traffic and abrasive conditions, three (3) coats or more are recommended. Allow product to dry before recoating; sand lightly between coats and remove sanding dust with a tack rag. Allow finish to cure for at least 24 hours before subjecting to normal use. Allow finish to fully cure (approximately 72 hours) before using wax or cleaners.

**SPREADING RATE:** May vary depending on surface porosity, application method, and material loss during application.

Recommended DFT per coat ..... 1 to 1.5 mils

Spread rates @ Rec. DFT.....385 to 578 ft<sup>2</sup>/gal

**DRYING TIME:** SUPER VARNISH will dry to touch in three to four hours, depending on temperature and humidity. Recoat after six hours.

**CLEAN UP:** Clean up with mineral spirits.

MAX. VOC: 458 grams/liter (3.82 lbs/gal)

### **WARNING! COMBUSTIBLE LIQUID AND VAPOR.**

**CONTAINS PETROLEUM DISTILLATE. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES NOSE, THROAT, EYE, AND SKIN IRRITATION. NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat and flame. **Use only with adequate ventilation.** Close container after each use. Avoid prolonged contact with eyes, skin, clothing, and vapors. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN. FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. If swallowed, do not induce vomiting. Call physician immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

---

### **Limited Warranty**

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

---

OLD MASTERS®  
1900 ALBANY PLACE SE  
ORANGE CITY, IA 51041