



1900 Albany Place SE
P.O. Box 286
Orange City, IA 51041

800-737-3436 Fax 712-737-3893
www.oldmastrs.com

PRODUCT INFORMATION

STAIN CONTROLLER

PRODUCT NO.	50101, 50104, 50116
GENERIC TYPE	Prestain clear wood sealer
COLOR	Clear
GLOSS	Not applicable
SOLIDS BY WEIGHT	20%
SOLIDS BY VOLUME	16 to 17%
V.O.C.	720 grams/liter
THEORETICAL COVERAGE @ 1 MIL DFT	260 sq. ft. per gal.
COVERAGE @ RECOMMENDED DFT	Not applicable
RECOMMENDED DFT PER COAT	Not applicable
WEIGHT PER GALLON	6.7 to 6.8 lbs.
FLASH POINT	86°F Tag Closed Cup
USE	For uniform stain application on soft woods like pine.
VISCOSITY AT 77°F	30 sec. #2 Ford Cup
AVERAGE DRY TIME AT 70°F & 50% R.H.	1 to 2 hours
RECOMMENDED THINNER	Thinning not recommended. Use as packaged.
APPLICATION	Apply with bristle brush. May be rolled or sprayed.
SURFACE PREPARATION	The surface must be clean and dry, and free from wax and surface residue.
CLEAN UP	Mineral spirits

FOR THE LOVE OF WOOD®

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



PRODUCT INFORMATION

STAIN CONTROLLER

DESCRIPTION: OLD MASTERS® STAIN CONTROLLER is a pre-stain clear wood sealer which helps control blotchiness of stains used on soft woods, such as fir, pine, or hemlock. Softer woods generally accept stains in various degrees which can make the stain appear uneven. With a pre-stain treatment of STAIN CONTROLLER, this variance of stain acceptance can be better controlled. Either oil or water based stains may be applied over our STAIN CONTROLLER. It is excellent for use on soft woods which are being stained with or adjacent to hardwoods. NOTE: This product does not take the place of sanding sealer in its usage. It is a pre-stain treatment only.

THINNING: Do not thin. Use as packaged.

SURFACE PREPARATION: Refinish Work: Strip the surface completely down to bare wood with paint and varnish remover, making sure all previous finishes are removed; then proceed as if new wood.

New Work: The surface to be treated must be clean, dry, and free of any wax or surface residue. Wax may be removed with fine steel wool saturated with paint thinner or alcohol. Sand lightly before applying product and remove dust.

APPLICATION: Stir product thoroughly with a circular, lifting motion. Apply with a polyester or nylon brush. Wait 5 to 15 minutes to allow penetration of product and then remove excess by wiping with a clean dry rag. The idea is not to leave a surface film, thus work in a small enough area so product cannot set up.

★ **Note:** Color depth may vary according with type of wood, stain and application technique. To assure that your finished color is what you want, we highly recommend you test your technique, wood stain, and wood type before you start your project.

SPREADING RATE: Approximately 100 to 125 square feet per quart depending upon method of application and type and porosity of wood.

DRYING TIME: Do not allow to dry thoroughly. Stain should be applied over STAIN CONTROLLER within two hours.

CLEAN UP: Clean up with mineral spirits or paint thinner.

MAX. VOC: 720 grams/liter (6 lbs/gal)

DANGER!

FLAMMABLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED.

CONTAINS PETROLEUM DISTILLATE.

VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES NOSE, THROAT, EYE, AND SKIN IRRITATION. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat and flame. **Use only with adequate ventilation.** Close container after each use. Avoid prolonged contact with eyes, skin, clothing, and vapors. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN. FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. If swallowed, do not induce vomiting. Call physician immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

Limited Warranty

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

OLD MASTERS®
1900 ALBANY PLACE SE
ORANGE CITY, IA 51041