



1900 Albany Place SE
P.O. Box 286
Orange City, IA 51041

800-747-3436 Fax 712-737-3893
www.oldmastrs.com

PRODUCT INFORMATION

H₂O[®] ACRYLIC VARNISH SATIN

PRODUCT NO.	75101, 75104, 75105
GENERIC TYPE	Acrylic Latex Varnish
COLOR	Clear
GLOSS	38 to 42 @ 60°
SOLIDS BY WEIGHT	34.0%
SOLIDS BY VOLUME	31.0%
V.O.C.	Less than 275 grams/liter
THEORETICAL COVERAGE @ 1 MIL DFT	530 sq. ft. per gal.
COVERAGE @ RECOMMENDED DFT	265 to 530 sq. ft.
RECOMMENDED DFT PER COAT	1 to 2 Mils
WEIGHT PER GALLON	8.58 lbs.
FLASH POINT	Not applicable
USE	Formulated for use on new or previously coated interior wood or painted surfaces. Do not use on floors.
VISCOSITY AT 77°F	45 sec. #4 Ford Cup
AVERAGE DRY TIME AT 70°F & 50% R.H.	10 to 15 minutes dry to touch, tack free in 1 hour, dry thoroughly in 2 hours.
RECOMMENDED THINNER	Water
APPLICATION	Brush, pad, roll or spray. Thinning with approximately 1 pint of water per gallon may be needed for spray application.
SURFACE PREPARATION	The surface must be clean, dry and free of wax, oil and grease. Remove all sanding dust with a rag dampened with water.
CLEAN UP	Soap and water.

FOR THE LOVE OF WOOD[®]

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



PRODUCT INFORMATION

H₂O[®] ACRYLIC VARNISH SATIN

DESCRIPTION: OLD MASTERS[®] H₂O[®] ACRYLIC VARNISH is a crystal clear water reducible finish for most interior wood surfaces **except floors**. OLD MASTERS[®] technology has produced a superior product with fast dry, low odor, good protection and full-bodied brushability. Its crystal clarity, exceptional flow and leveling reveal the natural finish of the wood and enhance the beauty of stained and natural grain. One coat of sealer and two coats of ACRYLIC VARNISH is usually adequate for superior beauty and protection of most surfaces. It does not yellow with aging when used as a protective clear coating over **waterborne stains** and **latex** painted surfaces.

THINNING: If necessary, it may be thinned with approximately one pint of water per gallon, as needed for spray application.

SPREADING RATE: Recommended rate of application is 300-350 square feet per gallon.

CLEAN UP: Wash brushes and equipment in warm, soapy water and rinse with water.

DRYING TIME: At 50% relative humidity and 70°F, H₂O[®] ACRYLIC VARNISH will dry to touch in 10 to 15 minutes; dry tack free within one hour and dry thoroughly within two to four hours. May be recoated in one hour.

SURFACE PREPARATION: All wood surfaces, bare wood or old finishes must be clean, dry and free from dirt, wax or grease. Sand new wood thoroughly with very fine grit sandpaper. Always sand in the direction of the wood grain. Previously finished surfaces should also be sanded with a fine grit sandpaper to remove imperfections and gloss. Be sure to remove all dust particles with a rag dampened with water before coating.

APPLICATION: DO NOT SHAKE! All finishes, especially the Satin Finish, should be stirred well before using and during use to ensure even gloss uniformity. H₂O[®] ACRYLIC VARNISH appears milky in the can but will dry clear. It may be brushed, rolled or sprayed. If necessary, it may be thinned with approximately one pint of water per gallon, as needed for spray application. Apply in full, even coats; if brushing, apply liberally and keep a wet edge, working quickly to insure an even coat. Large, flat surfaces may be rolled and quickly leveled off with a brush.

On new wood, seal with one coat of H₂O[®] ACRYLIC VARNISH or OLD MASTERS[®] H₂O[®] ACRYLIC SANDING SEALER. Allow to dry and sand carefully. Coat with one or two coats of H₂O[®] ACRYLIC VARNISH with one hour dry time between coats, sanding between coats for maximum smoothness. Be careful to remove all sanding dust! This dust will not redissolve into additional coats and will appear as dirt in the final finish. Use a clean rag dampened with water to pick up dust. May be used over solvent/oil based stains provided they are completely dry before application of H₂O[®] ACRYLIC VARNISH. **Many waterborne clears may have a tendency to yellow over solvent/oil based white or pastel colored stains. Please use caution and test before you start your project.**

HELPFUL ADVICE: We recommend applying when air and surface temperatures are between 60°F and 90°F, and humidity is between 30% and 70%.

H₂O[®] ACRYLIC VARNISH is non-toxic and environmentally friendly.

MAX VOC: 450 grams/liter (3.75 lbs/gal)

CAUTION!

Do not take internally. Close container after each use.
KEEP OUT OF REACH OF CHILDREN. Protect from freezing.

Limited Warranty

Since Old Masters[®] does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters[®] liability will under no circumstances exceed replacement of the product.

OLD MASTERS[®]
1900 ALBANY PLACE SE
ORANGE CITY, IA 51041