



1900 Albany Place SE
 P.O. Box 286
 Orange City, IA 51041

800-737-3436 Fax 712-737-3893
 www.oldmastrs.com

PRODUCT INFORMATION

CLEAR WOOD FINISH — SEMI-GLOSS

PRODUCT NO.	92801, 92804, 92805, 92808, 92810
GENERIC TYPE	Nitrocellulose Brushing/Spraying Lacquer
COLOR	Clear
GLOSS	55 to 65 @ 60°
SOLIDS BY WEIGHT	27 to 28%
SOLIDS BY VOLUME	18 to 19%
V.O.C.	680 grams/liter
THEORETICAL COVERAGE @ 1 MIL DFT	300 sq. ft. per gal.
COVERAGE @ RECOMMENDED DFT	150 to 300 sq. ft. per gal.
RECOMMENDED DFT PER COAT	1 to 2 Mils
WEIGHT PER GALLON	7.8 to 7.9 lbs.
FLASH POINT	66°F
USE	A fast drying finish for use on all interior bare or stained wood surfaces.
VISCOSITY AT 77°F	20 to 25 sec. #2 Zahn Cup
AVERAGE DRY TIME AT 70°F & 50% R.H.	Dry touch in 30 minutes. Recoat after 2 hours.
RECOMMENDED THINNER	Do not thin.
APPLICATION	Apply with brush, pad, or sprayer. Flow on liberally with the grain. Apply a minimum of 3 coats.
SURFACE PREPARATION	Surface must be clean, dry, and free from dirt, dust, wax, and grease. Sand wood smooth and remove dust. When applying over previously finished surfaces, test for compatibility. If lifting occurs, remove old finish and refinish as bare wood.
CLEAN UP	Lacquer Thinner

FOR THE LOVE OF WOOD®

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



PRODUCT INFORMATION

CLEAR WOOD FINISH — SEMI-GLOSS

DESCRIPTION: OLD MASTERS® CLEAR WOOD FINISH is a crystal clear, non-yellowing, interior nitrocellulose lacquer. It is easy to apply by brush or spray, and self-levels without brush marks. CLEAR WOOD FINISH is alcohol and water resistant, and can be easily repaired and recoated at any time without removing the old finish. Its fast drying formula allows multiple coat, one-day finishing of cabinets, doors, trim, bar tops, furniture (including baby furniture), and craft projects. It is also ideal for protecting brass and other interior metals from oxidation. Non-toxic when dry.

THINNING: Do not thin. Use as packaged.

SURFACE PREPARATION: The wood surface must be clean, dry, and free from dirt, dust, wax, and grease. **Surfaces must be properly prepared prior to application of this product.**

Bare Wood Surfaces: Eliminate imperfections by sanding the wood thoroughly; begin with a medium grit sandpaper progressing to a fine grit. Always sand in the direction of the woodgrain. Remove dust particles with a tack rag. If stain is to be applied, apply prior to using CLEAR WOOD FINISH, and allow the stain to dry thoroughly.

Previously Finished Surfaces: Sand with a fine grit sandpaper to remove surface imperfections and gloss. Remove sanding dust with a tack rag. Wax and/or polish are best removed by wiping thoroughly with mineral spirits. Change rags often and wash until all wax and/or polish is removed. Before finishing such surfaces, apply

CLEAR WOOD FINISH on an inconspicuous area. If wrinkling or lifting of the old finish occurs, remove with a wax-free paint remover and refinish as a bare wood surface.

APPLICATION INSTRUCTIONS: Stir well before and during use. Do not shake or thin. For projects requiring more than one container, intermix to ensure gloss uniformity. Apply finish with brush, pad, or spray gun. Flow on generously with minimum brushing to achieve a glass-like finish. Maintain a full wet brush, flowing with the grain. Sanding is not necessary between coats unless surface feels rough. If necessary, sand with very fine sandpaper and remove dust. Allow at least two hours between coats. A minimum of three coats is recommended for ultimate protection. In high moisture areas, apply up to 6 coats to prevent white water spotting. Allow finish to cure for at least 24 hours before subjecting to normal use.

SPREADING RATE: May vary depending on surface porosity, application method, and material loss during application.

Recommended DFT per coat 1 to 1.5 mils

Spread rates @ Rec. DFT..... 200 to 300 ft²/gal

DRYING TIME: CLEAR WOOD FINISH will dry to touch in 30 minutes, depending on temperature and humidity. Recoat after two hours.

CLEAN UP: Clean up with lacquer thinner.

MAX. VOC: 680 grams/liter (5.67 lbs/gal)

WARNING!

FLAMMABLE LIQUID AND VAPOR. VAPOR HARMFUL.

CAUSES EYE AND SKIN IRRITATION. HARMFUL IF SWALLOWED.

Contains: Methyl Amyl Ketone, Xylene, Methyl Isobutyl Ketone, Butyl Alcohol, Isobutyl Isobutyrate, Diethylene Glycol Butyl Ether, Isopropyl Alcohol, Methyl Ethyl Ketone, and Ethylbenzene. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES NOSE, THROAT, AND LUNG IRRITATION. MAY BE HARMFUL IF ABSORBED THROUGH SKIN. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat, sparks, and flame. VAPORS MAY CAUSE FLASH FIRE. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN.** **First Aid:** In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. (Thoroughly clean contaminated shoes.) If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

Limited Warranty

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

OLD MASTERS®
1900 ALBANY PLACE SE
ORANGE CITY, IA 51041